



NOTES:

1. MATERIAL: LOW CARBON STEEL
2. NOMINAL TENSILE: 115,000 P.S.I.
3. VOIDS IN RINGS OPTIONAL
4. WITHDRAWAL COATING ON SHANK. COATING ON HEAD IS PERMISSIBLE.
5. HOT DIPPED GALVANIZED AND COATED.
6. NAILS ARE TO BE GALVANIZED IN ACCORDANCE WITH ASTM A153 .
7. THE COATING WEIGHT SHALL BE 1.0 OZ/FT2 .

A	RELEASED FOR CUSTOMER DRAWING	61412	SIC 7/14/2015	CXW 7/14/2015	-	-
REV	DESCRIPTION	ECD NO.	REVISED/ DATE	ENGR/ DATE	MFG/ DATE	METLGST/ DATE
DIMENSIONS AND TOLERANCING IS IN ACCORDANCE WITH ANSI Y14.5M - 1982		THIRD ANGLE PROJECTION		DO NOT SCALE - WORK TO DRAWING OR MODEL DIMENSIONS ONLY ALL DIMENSIONS ARE IN MILLIMETERS		
DRAWN/DATE CXC 7/14/2015	MFG/DATE -	PROPRIETARY AND CONFIDENTIAL NO PORTION OF THIS DRAWING MAY BE QUOTED OR REPRODUCED IN ANY FORM WITHOUT THE EXPRESS WRITTEN PERMISSION OF:		 BOSTITCH FASTENING SYSTEMS 701 E. Joppa Road Towson, Maryland 21286		
CHK'D/DATE CXW 7/14/2015	METLGST/DATE -	RELEASE ECD 61412	DESCRIPTION RING SHANK NAIL CUSTOMER DRAWING			
ENGR/DATE CXW 7/14/2015	SCALE 1:1		SHEET SIZE A4		PART NUMBER 9R209675	REVISION A

RH-S10DR131HDG	.800	3.000
PART NO.	DIM "A"	LENGTH "B"